



# Specifications

<b>Base Model Number</b>	OMNIKEY® 5325 CL
<b>Dimensions</b>	3.78" x 3.07" x .031" (115 x 96.5 x 25.5 mm)
<b>Weight</b>	Approx. 5.01 oz (142 g)
<b>Power supply</b>	Bus powered
<b>Operating temperature</b>	32°-131° F (0° - 55° C)
<b>Operating humidity</b>	10-90% rH
<b>HOST INTERFACE</b>	
<b>Host Interface</b>	USB 2.0 CCID <sup>1</sup> (also compliant with USB 1.1)
<b>Transmission speed</b>	12 Mbps (USB 2.0 full speed)
<b>Protocols</b>	T=0, T=1, 2-wire: SLE 4432/42 (S=10), 3-wire: SLE 4418/28 (S=9), I <sup>2</sup> C (S=8)
<b>Card size</b>	ID-1 (full-size)
<b>Proximity card interface frequency</b>	HID Prox 125 kHz
<b>Supported APIs</b>	PC/SC driver, CT-API (on top of PC/SC, for contact interface), OCF (on top of PC/SC, for contact interface), Synchronous API (on top of PC/SC, for contact interface)
<b>PC/SC Driver Support</b>	Windows® 2000 / XP (32bit), 2003 Server, 2008 Server, Windows® CE 5.0 / CE.NET / CE 6.0 (depending on hardware), Windows® XP 64bit, Windows® Vista (32bit / 64bit), Windows 7 (32bit / 64bit), Linux® and Mac® OS X
<b>Status indicator</b>	Dual-color LED (green=ready, red=busy)
<b>Color</b>	Dark Grey
<b>Options</b>	<b>Customer specific logo, label or color:</b> Available upon request
<b>Reader Board</b>	Available as PCB
<b>Composition</b>	ABS
<b>Connector cable</b>	70.9" (180 cm)
<b>Meantime between failure (MTBF)</b>	500,000 hours
<b>Compliance / Certification</b>	Microsoft® WHQL <sup>3</sup> , EMV <sup>2</sup> 2000 Level 1, ISO 7816, HBCI <sup>4</sup> , USB 2.0 (USB 1.1 compatible), CCID <sup>1</sup> (contact interface only), GSA FIPS 201 approved product list (in preparation)
<b>Safety / Environmental</b>	CE, FCC, UL, C-Tick, RoHS, WEEE
<b>Warranty</b>	Two year manufacturer's warranty. (For drivers, see complete lifetime support policy.)

1 = Chip Card Interface Device 2 = Europay® MasterCard® Visa® 3 = Windows® Hardware Quality Lab 4 = Home Banking Computer Interface



kkk"WfWXYaYI]Wc"Wca"a l  
\$% , \$\$ -% & % & +&

**ACCESS** experience.

© 2010 HID Global Corporation. All rights reserved. HID, the HID logo, Omnikey and the Omnikey logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 07/2010

MKT-OMNIKEY\_5325CL\_DS-EN

hidglobal.com

**Corporate North America**  
15370 Barranca Pkwy  
Irvine, CA 92618  
U.S.A.  
Tel: 1 800 237 7769  
Tel: +1 949 732 2000  
Fax: +1 949 732 2360

**Asia Pacific**  
19/F 625 King's Road  
North Point  
Island East  
Hong Kong  
Tel: +852 3160 9800  
Fax: +852 3160 4809

**Latin America**  
Circunvalación Ote. #201 B  
Despacho 2  
Col. Jardines del Moral  
Leon 37160, Gto.  
Mexico  
Tel: +52 477 779 1492  
Fax: +52 477 779 1493

**Europe, Middle East & Africa**  
Haverhill Business Park  
Phoenix Road  
Haverhill, Suffolk  
CB9 7AE  
England  
Tel: +44 1440 714 850  
Fax: +44 1440 714 840