

OMNIKEY® 532I CLi USB Reader

Contactless USB Smart Card Reader

- ▶ Versatile Desktop Applications – Ideal for end-user environments using contactless HID iCLASS® technology
- ▶ Fast Contactless Transmission – Supports fastest ISO standard transmission modes
- ▶ Designed for User Convenience – Housing design is optimized for advanced contactless applications
- ▶ Readily compliant – Seamless integration with HID on the Desktop™ and other applications



ACCESS identification.

The OMNIKEY® 532I CLi USB smart card reader represents the ideal contactless HID iCLASS® reader in a convenient desktop device. Reading and writing to any contactless HID iCLASS card, the device economically supports desktop clients where contactless iCLASS technology is used.

Utilizing contactless smart card technology for PC-linked applications, the OMNIKEY 532I CLi allows users to experience the convenience, speed and security of HID iCLASS contactless technology for applications such as iCLASS on the Desktop™.

The OMNIKEY 532I series readers work seamlessly with iCLASS-enabled logical access applications in combination with naviGO™ software, which is part of the HID on the Desktop solution. naviGo is a cost-effective solution that simplifies deployment of strong authentication managing and automating the lifecycle of strong authentication user credentials on iCLASS smart cards. Designed to enable HID on the Desktop™, naviGO allows card holders to manage their own enrollment, PIN management and knowledge-based authentication through a self-service browser based application.

- ▶ Secure authentication device for logging on to PC or IT infrastructure
- ▶ Does not require organizations using iCLASS to re-badge, issue a new token or make any changes to their physical access control system
- ▶ Easy to install and can be used with naviGo software to converge access from the door to the logging onto PCs
- ▶ Compliant with all relevant safety and environmental standards, including CE, FCC, UL, RoHS and WEEE

For actual driver downloads please visit www.hidglobal.com/omnikey

Specifications

Base Model Number	OMNIKEY® 5321 CLI
Dimensions	3.78" x 3.07" x 0.31" (115 x 96.5 x 25.5 mm)
Weight	Approx. 5.64 oz. (160 g.)
Power supply	Bus powered
Operating temperature	32°-131° F (0° - 55° C)
Operating humidity	10 - 90% rH
HOST INTERFACE	
Host Interface	USB 2.0 (also compliant with USB 1.1)
Transmission speed	12 Mbps (USB 2.0 full speed)
CONTACTLESS SMART CARD INTERFACE	
Protocols	HID iCLASS®
Driver Support	Windows 2000, Windows XP (32bit / 64bit), Windows 2003/2008 Server, Windows® CE 5.0 / 6.0 / CE.NET (depending on hardware), Windows® Vista (32bit / 64bit), Windows® 7 (32bit / 64bit), Linux®
Status indicator	Dual color LED (green=ready, red=busy)
Color	Grey
Options	Customer Specific Logo and Colors: Available upon request
Composition	ABS
Meantime between failure (MTBF)	500,000 hours
Compliance / Certification	Microsoft® WHQL ¹ , USB 2.0 (USB 1.1 compatible)
Safety / Environmental	CE, FCC, UL, RoHS, WEEE
Warranty	Two (2) year manufacturer's warranty. (For drivers, see complete lifetime support policy.)

1 = Windows® Hardware Quality Lab



5@dO55d @dY@dMY

d

d

© 2010 HID Global Corporation. All rights reserved. HID, the HID logo, Omnikey and the Omnikey logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 07/2010

MKT-OMNIKEY_5321_CLI_DS_EN Rev. 07/2010

ACCESS experience.

hidglobal.com

HID Global Offices:

Corporate North America
 15370 Barranca Pkwy
 Irvine, CA 92618
 U.S.A.
 Tel: 1 800 237 7769
 Tel: +1 949 732 2000
 Fax: +1 949 732 2360

Asia Pacific
 19/F 625 King's Road
 North Point
 Island East
 Hong Kong
 Tel: +852 3160 9800
 Fax: +852 3160 4809

Latin America
 Circunvalación Ote. #201 B
 Despacho 2
 Col. Jardines del Moral
 Leon 37160, Gto.
 Mexico
 Tel: +52 477 779 1492
 Fax: +52 477 779 1493

Europe, Middle East & Africa
 Haverhill Business Park
 Phoenix Road
 Haverhill, Suffolk
 CB9 7AE
 England
 Tel: +44 1440 714 850
 Fax: +44 1440 714 840