

# OMNIKEY® 5321 CR USB Reader

Waterproof Contactless USB Smart Card Reader for Hygienic Environments

- ▶ **Designed for User Convenience** – Innovative and stylish housing design for easy contactless operation in clean room and germ-free environments
- ▶ **Versatile Applications** – Ideal for end-user environments where a wide range of contactless smart card technologies are in use
- ▶ **Fast Contactless Transmission** – Supports contactless smart cards up to 848 Kbps in fastest ISO 14443 A/B
- ▶ **Readily Compliant** – Supports HID® iCLASS® and MIFARE®, as well as ISO 14443 A/B and ISO 15693



## SECURE identification.

Finished in a stylish, waterproof housing, the OMNIKEY® 5321 CR reader is ideal for contactless technology applications with high demands for hygiene, such as for manufacturing sites, hospitals, clean room environments or anywhere that a sleek and modern reader is desired. A PC-linked reader that reads/writes to 13.56 MHz contactless smart cards in all three HF standards, the OMNIKEY 5321 CR economically supports end-user environments where a variety of contactless cards and tags are used.

Utilizing contactless smart card technology for PC-linked applications, the OMNIKEY® 5321 CR device allows users to experience the convenience, speed and security of contactless technology for applications, including log-on to Windows®, networks, web sites and applications for the secure storage of user names, passwords and personal information.

Additionally, the OMNIKEY 5321 CR supports HID on the Desktop™ as part of a three component solution, including a HID technology card, reader and naviGO® software, enabling logical access in hygienic or virtually any environment. Equally suited for mobile and laptop usage, the reader supports all relevant operating systems, ensuring worldwide compliance and easy integration in any system.

- ▶ Uniquely designed sealed housing supports clean room requirements
- ▶ Supports three ISO standards for contactless cards (ISO 14443 A/B and 15693) and Microsoft WHQL
- ▶ Supports contactless smart cards with up to 848 Kbps in the fastest ISO 14443 transmission mode
- ▶ Standard application interfaces include PC/SC, Synchronous-API (on top of PC/SC)
- ▶ EMD suppression capabilities, allow high transmission speed and full secure read support for smart cards and passports.

Contactless smart cards supported:

- ▶ HID: iCLASS®
- ▶ NXP: MIFARE®, MIFARE Plus, DESFire®, SMART-MX and ICODE
- ▶ Texas Instruments: TagIT®
- ▶ ST Micro: x-ident, SR 176, SR 1X 4K
- ▶ Infineon: my-d™ (in secure mode UID only)
- ▶ Atmel: AT088RF020
- ▶ KSW MicroTech: KSW TempSens
- ▶ iCODE SLI, iCODE SL2 & LRI 64
- ▶ Contactless 2048-bit key generation in RSA mode (JCOP/SMART-MX)

For drivers download, please visit <http://www.hidglobal.com/omnikey>

# Specifications

<b>Base Model Number</b>	OMNIKEY® 5321 CR USB
<b>Dimensions</b>	4.72" x 3.54" x 0.94" (120 x 90 x 24 mm)
<b>Weight</b>	Approx. 7.48 oz / 212 g
<b>Power supply</b>	Bus powered
<b>Housing protection class</b>	IP67
<b>Operating temperature</b>	32°-131° F (0° - 55° C)
<b>Operating humidity</b>	10-90% rH
<b>HOST INTERFACE</b>	
<b>Host Interface</b>	USB 2.0 (also compliant with USB 1.1)
<b>Transmission speed</b>	12 Mbps (USB 2.0 full speed)
<b>CONTACTLESS SMART CARD INTERFACE</b>	
<b>Protocols</b>	T=CL, MIFARE®, iCLASS® / ISO 14443 A with 848 Kbps transmission rate (depending on card) ISO 14443 B with 848 Kbps transmission rate (depending on card) ISO 15693 with 26 Kbps transmission rate (depending on card)
<b>Supported APIs</b>	PC/SC driver (ready for 2.01), Synchronous API (on top of PC/SC))
<b>PC/SC Driver Support</b>	Windows® 2000 / XP (32 bit/64 bit), Server 2003, 2008, 2008 R2, Windows® CE 5.0 / 6.0 / 6.5 (depending on hardware), Windows Vista (32 bit/64 bit), Windows 7 (32 bit/64 bit) Linux®, Mac® OS X 10.5/10.6 (in preparation)
<b>Status indicator</b>	Dual color LED (green=ready, red=busy)
<b>Reader Board</b>	Also available as PCB
<b>Color</b>	White
<b>Options</b>	<b>Customer Specific Logo:</b> Available upon request
<b>Composition</b>	PC
<b>Connector cable</b>	70.9" (180 cm)
<b>Meantime between failure (MTBF)</b>	500,000 hours
<b>Compliance / Certification</b>	Microsoft WHQL <sup>1</sup> , Ingress Protection Class IP67, ISO 14443A+B, ISO 15693
<b>Safety / Environmental</b>	CE, FCC, UL, RoHS, WEEE
<b>Warranty</b>	Two year manufacturer's warranty. (For drivers, see complete lifetime support policy.)

<sup>1</sup> = Windows® Hardware Quality Lab.



**CRC de México S.A. de C.V.**  
[www.crcdemexico.com.mx](http://www.crcdemexico.com.mx)  
 01 800 91 21 272

© 2010 HID Global Corporation. All rights reserved. HID, the HID logo, Omnikey and the Omnikey logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 05/2010

MKT-OMNIKEY\_5321\_CR\_DS\_EN Rev. 05/2010

**ACCESS experience.**

[hidglobal.com](http://hidglobal.com)

**HID Global Offices:**

**Corporate North America**  
 15370 Barranca Pkwy  
 Irvine, CA 92618  
 U.S.A.  
 Tel: 1 800 237 7769  
 Tel: +1 949 732 2000  
 Fax: +1 949 732 2360

**Asia Pacific**  
 19/F 625 King's Road  
 North Point  
 Island East  
 Hong Kong  
 Tel: +852 3160 9800  
 Fax: +852 3160 4809

**Latin America**  
 Circunvalación Ote. #201 B  
 Despacho 2  
 Col. Jardines del Moral  
 Leon 37160, Gto.  
 Mexico  
 Tel: +52 477 779 1492  
 Fax: +52 477 779 1493

**Europe, Middle East & Africa**  
 Haverhill Business Park  
 Phoenix Road  
 Haverhill, Suffolk  
 CB9 7AE  
 England  
 Tel: +44 1440 714 850  
 Fax: +44 1440 714 840